



THE FUTURE OF BUSINESS COMMUNICATION, DELIVERED TODAY

MOTOTRBO™ DIGITAL TWO-WAY PORTABLE RADIOS

Make technology more productive and personal. You asked for a forward-thinking way to connect your people to their work, wherever they go. An innovative business tool that increases their efficiency while lowering your costs. Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. It integrates voice and data seamlessly, offers enhanced features that are easy to use and delivers increased capacity to meet your communication needs from the field to the factory floor. With exceptional voice quality and long battery life, MOTOTRBO keeps your work teams connected when communication is a must.

HIGH-POWERED PERFORMANCE

Because MOTOTRBO uses TDMA digital technology, it delivers integrated voice and data, twice the calling capacity plus clearer voice communications. When it comes to battery performance, MOTOTRBO radios operate 40 percent longer between recharges compared to analog. In fact, the leading-edge IMPRES™ technology in our batteries, chargers and audio accessories also ensures longer talk time and clearer audio.

INDUSTRY-LEADING APPLICATIONS

Motorola's Application Developer Program offers customized data applications so you can adapt your radios to your unique business needs. Because we've created the largest developer program in the industry, we can provide nimble applications that address your challenges and answer your objectives – from work order ticket management to network management, email gateways to location tracking, dispatch consoles to telephony integration, and beyond.

Whether you want to send text messages or track work order information, pinpoint work crew locations with integrated GPS or manage your fleet from a central dispatch location, MOTOTRBO paves the way – with customizable data applications on one convenient device.



ADDED FUNCTIONALITY

MOTOTRBO offers added functionality, including dispatch capability with the MIP 5000 VoIP console, enhanced call signaling, basic and enhanced privacy-scrambling, option board expandability and compatibility with SCADA solutions for utility and public service monitoring and alarms. Plus digital telephone interconnect capability to enable communication between radios and landline or mobile phones as well as a transmit interrupt suite – with voice interrupt, emergency voice interrupt or data over voice interrupt – to prioritize critical communication the moment you need it.

EXPANDED CAPACITY AND COVERAGE

Your workforce is hard at work every day – picking up loads, making road repairs, providing security, responding to guest requests or restoring power after a storm. That’s why you need the proven performance of MOTOTRBO radio systems for non-stop communication no matter the size of your work force, no matter where they go.

MOTOTRBO’s IP Site Connect dramatically improves customer service and productivity by using the Internet to extend coverage to users anywhere in the world. Our scalable, single-site Capacity Plus solution expands capacity to over 1,000 users without adding new frequencies. Connect Plus multi-site digital trunking enables you to

accommodate the high volume, wide area communication your business requires. Whether you need coverage at a single site or across multiple sites, MOTOTRBO can be scaled to meet your needs.

MIGRATE AT YOUR OWN PACE

Keeping operations running smoothly during a change in communication systems is vital to your business. It’s easy to migrate to digital with MOTOTRBO because radios operate in analog and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analog and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analog system, and when your time and budget allow you can begin migrating to digital at your own pace.



RELIABLE DURABILITY

MOTOTRBO meets the most demanding specs, including IP57 for water submersibility (portables) and U.S. Military 810 C, D, E and F. It’s “intrinsically safe” when purchased and equipped with an FM/CSA battery, for use where flammable gas, vapors or combustible dust may be present. And backed by a two-year Standard Warranty, one-year Repair Service Advantage (US)/Extended Warranty (Canada) and minimum 1-year warranty for accessories.



PRODUCT SPEC SHEET
MOTOTRBO™ XPR™ 6550/XPR 6350 PORTABLE RADIOS

GENERAL SPECIFICATIONS

	DISPLAY XPR 6550			NON-DISPLAY XPR 6350		
	VHF	UHF Band I	UHF Band II	VHF	UHF Band I	UHF Band II
Channel Capacity		Up to 1,000			32	
Frequency	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz
Dimensions		5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)			5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)	
Weight (with IMPRES Li-Ion 1500 mAh Battery) (with IMPRES Li-Ion 1400 mAh FM Battery) (with IMPRES Li-Ion 2150 mAh Battery) (with NiMH 1300 mAh Battery)		12.7 oz (360 g) 13 oz (370 g) 13.17 oz (375 g) 15.2 oz (430 g)			11.63 oz (330 g) 11.98 oz (340 g) 12.12 oz (345 g) 14.09 oz (400 g)	
Power Supply		7.5 V nominal			7.5 V nominal	
FCC Description	AZ489FT3815	AZ489FT4876	AZ489FT4884	AZ489FT3815	AZ489FT4876	AZ489FT4884
IC Description	109U-89FT3815	109U-89FT4876	109U-89FT4884	109U-89FT3815	109U-89FT4876	109U-89FT4884
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.						
IMPRES Li-Ion 1500 mAh Battery		Analog: 9 hrs Digital: 13 hrs			Analog: 9 hrs Digital: 13 hrs	
IMPRES Li-Ion 1400 mAh FM Battery		Analog: 8.5 hrs Digital: 12 hrs			Analog: 8.5 hrs Digital: 12 hrs	
IMPRES Li-Ion 2150 mAh Battery		Analog: 13.5 hrs Digital: 19 hrs			Analog: 13.5 hrs Digital: 19 hrs	
NiMH 1300 mAh Battery		Analog: 8 hrs Digital: 11 hrs			Analog: 8 hrs Digital: 11 hrs	
RECEIVER: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350				GPS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350		
Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)		
Channel Spacing		12.5 kHz / 25 kHz*		TTF (Time To First Fix) Cold Start	< 2 minutes	
Frequency Stability (-30° C, +60° C, +25° C)		+/- 0.5 ppm		TTF (Time To First Fix) Hot Start	< 10 seconds	
Analog Sensitivity (12dB SINAD)		0.35 uV 0.22 uV (typical)		Horizontal Accuracy	< 10 meters	
Digital Sensitivity		5% BER: 0.3 uV		MILITARY STANDARDS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350		
Intermodulation (TIA603C)		70 dB			810E	
Adjacent Channel Selectivity				Applicable MIL-STD	810F	
TIA603		60 dB @ 12.5 kHz, 70 dB @25 kHz*		Methods	Procedures	Methods
TIA603C		45 dB @ 12.5 kHz, 70 dB @25 kHz*		Low Pressure	500.3	II
Spurious Rejection (TIA603C)		70 dB		High Temperature	501.3	I/A, II/A1
Rated Audio		500 mW		Low Temperature	502.3	I/C3, II/C1
Audio Distortion @ Rated Audio		3% (typical)		Temperature Shock	503.3	I/A, 1C3
Hum and Noise		-40 dB @ 12.5 kHz -45 dB @ 25 kHz*		Solar Radiation	505.3	I
Audio Response		TIA603C		Rain	506.3	I, II
Conducted Spurious Emission (TIA603C)		-57 dBm		Humidity	507.3	II
				Salt Fog	509.3	I
				Dust	510.3	I
				Vibration	514.4	I/10, II/3
				Shock	516.4	I, IV
				ENVIRONMENTAL SPECIFICATIONS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350		
				Operating Temperature	-30° C / +60° C	
				Storage Temperature	-40° C / +85° C	
				Thermal Shock	Per MIL-STD	
				Humidity	Per MIL-STD	
				ESD	IEC-801-2KV	
				Dust and Water Intrusion	IEC 60529 - IP57	
				Packaging Test	MIL-STD 810D and E	
				Testing completed using portable radio with attached battery and antenna.		
				FACTORY MUTUAL APPROVALS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350		
				MOTOTRBO XPR Series portable radios have been certified by FM and CSA Approvals in accordance with Canada and U.S. Codes as intrinsically safe for use in Class I, II, III, Division 1, Groups C, D, E, F, G, when properly equipped with a Motorola FM approved battery option. They are also approved for use in Class I, Division 2, Groups A, B, C, D.		
				 		
4FSK Digital Modulation		12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE				
Digital Vocoder Type		AMBE +2™				
Digital Protocol		ETSI TS 102 361-1, -2, -3				

*25 kHz will not be available on new equipment in the U.S. after 1/1/2013.
**Radio only, Li-Ion battery -10° C; NiMH battery -20° C.
Specifications subject to change without notice. All specifications shown are typical.
Radio meets applicable regulatory requirements. Version 10 07/10

PRODUCT SPEC SHEET

MOTOTRBO™ XPR™ 6580/XPR 6380 PORTABLE RADIOS

GENERAL SPECIFICATIONS

	DISPLAY XPR 6580	NON-DISPLAY XPR 6380	MILITARY STANDARDS				
				810E		810F	
			Applicable MIL-STD	Methods	Procedures	Methods	Procedures
Channel Capacity	Up to 1000	Up to 32					
Frequency Band	800 and 900 MHz	800 and 900 MHz	Low Pressure	500.3	II	500.4	II
Dimensions (HxWxL) with Li-Ion Battery	5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)	5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)	High Temperature	501.3	I/A, II/A1	501.4	I/Hot, II/Hot
Weight with IMPRES Li-Ion 2150 mAh Battery	13.17 oz (375 g)	12.12 oz (345 g)	Low Temperature	502.3	I/C3, II/C1	502.4	I/C3, II/C1
Power Supply	7.5 V nominal	7.5 V nominal	Temperature Shock	503.3	I/A, 1C3	503.4	I
FCC Description	ABZ99FT5011	ABZ99FT5011	Solar Radiation	505.3	I	505.4	I
IC Description	109AB-99FT5011	109AB-99FT5011	Rain	506.3	I, II	506.4	I, III
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.			Humidity	507.3	II	507.4	—
IMPRES Li-Ion 2150 mAh Battery	Analog: 13 hrs / Digital: 17 hrs	Analog: 13 hrs / Digital: 17 hrs	Salt Fog	509.3	I	509.4	I
IMPRES Li-Ion 1400 mAh Battery	Analog: 9 hrs / Digital: 12 hrs	Analog: 9 hrs / Digital: 12 hrs	Dust	510.3	I	510.4	I

RECEIVER

Frequencies	800 MHz: 854-866 MHz and 869-870 MHz / 900 MHz: 935-941 MHz	Vibration	514.4	I/10, II/3	514.5	I/24
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz	Shock	516.4	I, IV	516.5	I, IV
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm	ENVIRONMENTAL SPECIFICATIONS				
Analog Sensitivity (12 dB SINAD) Typical	0.25 uV	Operating Temperature	-30° C / +60° C			
Digital Sensitivity	5% BER: 0.3 uV	Operating Temperature (w/ IMPRES Li-Ion battery)	-10° C to +60° C			
Intermodulation (TIA603C)	70 dB	Storage Temperature	-40° C to +85° C			
Adjacent Channel Selectivity (TIA603) - 1T	60 dB @ 12.5 kHz / 70 dB @ 25 kHz	Thermal Shock	Per MIL-STD			
Adjacent Channel Selectivity (TIA603C) - 2T	45 dB @ 12.5 kHz / 70 dB @ 25 kHz	Humidity	Per MIL-STD			
Spurious Rejection (TIA603C)	70 dB	ESD	IEC-801-2KV			
Rated Audio	.5 W	Dust and Water Intrusion	IEC 60529 - IP54			
Audio Distortion @ Rated Audio	3% (typical)	Packaging Test	MIL-STD 810D and E			
Hum and Noise	-40 dB @ 12.5 kHz / -45 dB @ 25 kHz	Testing completed using portable radio with attached battery and antenna.				
Audio Response	TIA603C	FACTORY MUTUAL APPROVALS				
Conducted Spurious Emission (ETSI)	-57 dBm	MOTOTRBO XPR Series portable radios have been certified by FM and CSA Approvals in accordance with Canada and U.S. Codes as intrinsically safe for use in Class I, II, III, Division 1, Groups C, D, E, F, G, when properly equipped with a Motorola FM approved battery option. They are also approved for use in Class I, Division 2, Groups A, B, C, D.				

TRANSMITTER

Frequencies	800 MHz: 809-821 MHz, 824-825 MHz, 854-866 MHz and 869-870 MHz 900 MHz: 896-902 MHz and 935-941 MHz
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz
Frequency Stability (-30° C, +60° C)	+/- 0.5 ppm
Low Power Output	1 W
High Power Output	2.5 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz / +/- 5.0 kHz @ 25 kHz
FM Hum and Noise	-40 dB @ 12.5 kHz / -45 dB @ 25 kHz
Conducted / Rated Emission (ETSI)	-36 dBm < 1 GHz / -30 dBm > 1 GHz
Adjacent Channel Power	-60 dB @ 12.5 kHz / -70 dB @ 25 kHz
Audio Response	TIA603C
Audio Distortion (per EIA)	3%
FM Modulation	12.5 kHz: 11K0F3E / 25 kHz: 16K0F3E
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD / 12.5 kHz Data & Voice: 7K60FXE
Digital Vocoder Type	AMBE +2™
Digital Protocol	ETSI TS 102 361-1, -2, -3

GPS

Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)	
TTF (Time To First Fix) Cold Start	< 2 minutes
TTF (Time To First Fix) Hot Start	< 10 seconds
Horizontal Accuracy	< 10 meters



ONLY THE FOLLOWING FREQUENCIES ARE SUPPORTED BY THE XPR 6580 / XPR 6380

Band	Receive	Transmit		
800 MHz	851.0125	806.0125	851.0125	
	851.5125	806.5125	851.5125	
	852.0125	807.0125	852.0125	
	852.5125	807.5125	852.5125	
	853.0125	808.0125	853.0125	
	854.000 - 865.9875	809.000 - 820.9875	854.000 - 865.9875	
	866.0125	821.0125	866.0125	
	866.5125	821.5125	866.5125	
	867.0125	822.0125	867.0125	
	867.5125	822.5125	867.5125	
	868.0125	823.0125	868.0125	
	869.000 - 870.000	824.000 - 825.000	869.000 - 870.000	
	900 MHz	935.000 - 941.000	896.000 - 902.000	935.000 - 941.000

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements. Version 2 07/10

For more information on how to make your business more efficient and better connected, visit www.motorola.com/mototrbo.

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. [motorolasolutions.com](http://www.motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2011 Motorola Solutions, Inc. All rights reserved. R3-4-2028B